

HIGH-FREQUENCY COMPOSITE COMPONENT

Publication number: JP10126307

Publication date: 1998-05-15

Inventor: FURUYA KOUJI; NAKAJIMA NORIO; SUZAKI HIDESHI

Applicant: MURATA MANUFACTURING CO

Classification:

- International: **H01P1/15**; **H04B1/44**; H05K1/00; H05K1/02; **H01P1/10**;
H04B1/44; H05K1/00; H05K1/02; (IPC1-7): H04B1/44;
H01P1/15

- European: H01P1/15

Application number: JP19960278075 19961021

Priority number(s): JP19960278075 19961021

Also published as:



EP0837516 (A2)
US5903421 (A1)
EP0837516 (A3)
EP0837516 (B1)
DE69727352T (T)

Report a data error he

Abstract of JP10126307

PROBLEM TO BE SOLVED: To provide the high-frequency composite component which is made small in size and made light in weight by integrating a high-frequency switch and an amplifier. **SOLUTION:** A high-frequency composite component 10 is made up of a high-frequency switch SW and a Tx side amplifier AMP 1 among high-frequency components of the PHS system. Then the high-frequency switch SW is used to switch the connection between the transmission circuit Tx and an antenna ANT and the connection between a reception circuit Rx and the antenna ANT. Moreover, the Tx side amplifier AMP 1 acts as an amplifier that amplifies a transmission signal converted into an RF signal and passing through a Tx side filter F1 to send the result to the high-frequency switch SW.

